

| | | |
|----------------|----------|-------|
| Submitted by: | | Date: |
| Type: | Project: | |
| Ordering Info: | | |

High Performance 3" Aperture (HP-3) Pendant

Indirect/Direct shown



HP-3 is a compact, streamlined, 3-inch-wide linear luminaire with recycled aluminum housing, advanced optics, and mid-power LEDs, delivering 90% of its initial light output for over 100,000 hours. It features an innovative assembly design, an easy-to-use joiner for continuous runs, and seamless installation. Backed by a 10-year warranty, it is available in 179 RAL color options to suit any project.


This product is enrolled in the International Living Future Institute (ILFI) Declare 2.0 Program and is third-party verified with options achieving **Red List Approved** and **Red List Declared** status.

Signal White is standard finish

CROSS SECTIONS

Indirect/Direct


Flush Uplight Diffuser
(standard)



Flush Downlight Diffuser
(standard)


OPTIC OPTIONS

Standard Uplight
Flush Optic (F)




Standard Downlight
Flush Optic (F)

Wide Spread Optic
(WSO)



Standard Downlight
Flush Optic (F)

Asymmetric Optic
(ASY)



Standard Downlight
Flush Optic (F)

COMING SOON



Recessed
(R)



Surface Mount
(SM)



Declare.



| | | |
|----------------|----------|-------|
| Submitted by: | | Date: |
| Type: | Project: | |
| Ordering Info: | | |

High Performance 3" Aperture (HP-3) Pendant

Ordering Guide Example: HP - 3 - P - ID - 36" - S - S - 835 - F - F - 96LG - 120 - DC - FC-10% - FA50 - C1 - FE - SW - LGD18W - OBO - CP

BODY TYPE

OUTPUT AND LED TYPE

| Platform | Series Name | Luminaire Type | Luminaire Distribution | Total Length of Run | Uplight Output (Flush) | Downlight Output (Flush) ¹ |
|-----------------------|-------------|----------------|------------------------|---|---|--|
| HP - High Performance | 3 | P - Pendant | ID - Indirect/Direct | Minimum 2' section length. Increments accurate to 1/16" (±1/32"), standard. 12' maximum section length. | S - Standard (428 lm/ft) B - Boosted (538 lm/ft) H - High (813 lm/ft) V - Very High (1045 lm/ft) TL - Tailored: _____ lm/ft* | S - Standard (379 lm/ft) B - Boosted (477 lm/ft) H - High (721 lm/ft) V - Very High (927 lm/ft) TL - Tailored: _____ lm/ft* |

Lumen provided above are for Flush lens only, see pg. 11 for WW lumens.
* Specify Tailored lm/ft of outputs between Standard (S) and Very High (V). Consult factory for tailored lumen output outside of this range.

OUTPUT AND LED TYPE

MECHANICAL/OPTICAL OPTIONS

ELECTRICAL OPTIONS

| LED CRI/CCT | Uplight Optics | Downlight Optics | Reflector System | Voltage |
|---|---|--|----------------------------------|--|
| 830 - 80 CRI, 3000K 835 - 80 CRI, 3500K 840 - 80 CRI, 4000K 930 - 90 CRI, 3000K ¹ 935 - 90 CRI, 3500K ¹ 940 - 90 CRI, 4000K ¹ 8TW - 80 CRI, Tunable White ¹ 9TW - 90 CRI, Tunable White ¹ | TG - Top Glow (coming soon) F - Flush (standard) ASY-L - Asymmetric Left Optic ASY-R - Asymmetric Right Optic WSO - Widespread Optic | F - Flush (standard) BG - Bottom Glow (coming soon) | 96LG - 96 Low Gloss White | 120 - 120 Voltage 277 - 277 Voltage 347 - 347 Voltage (OTi only) |
| | | | | Circuiting ² |
| | | | | SC - Single Circuit* One single circuit in a run DC - Dual Circuit* Independent control of up and down separately in an I/D style fixture MC - Multi-Circuit* More than one switch leg or zone. Factory shop drawings required * Battery, Night Light, and Emergency to Generator circuits are in addition to the normal luminaire circuit(s) |

ELECTRICAL OPTIONS

MOUNTING OPTIONS

OTHER OPTIONS

| Driver Selection | Mounting Method | Endcap Style | Finish |
|--|---|---|---|
| 0-10V Driver Options FC-10% - 0-10V 10% (standard) FC-1% - 0-10V 1% OTi-10% - EldoLED OTi, 0-10V 10% ³ OTi-1% - EldoLED OTi, 0-10V 1% ³ ELD-10V-0% - EldoLED SOLOdrive, 0-10V 0.1% 10V-TW-10% - EldoLED OTi, 0-10V 10% (Tunable White) ³ DALI Driver Options FC-DALI-1% - DALI 1% DXL-DALI-1% - EldoLED Dexal, 1% ELD-DALI-0% - EldoLED SOLOdrive, 0.1% ELD-DALI-TW - EldoLED DUALdrive LightShape, 0.1% (Tunable White) | DMX Driver Options ELD-DMX - EldoLED POWERdrive, 0.1% ELD-DMX-TW - EldoLED POWERdrive, 0.1% (Tunable White) Lutron Driver Options LUT-ES1 - Lutron, Ecosystem 1% LUT-TW - Lutron LD2 Dali-2 1% (Tunable White) See Page 3 for additional driver options and details | FA50 - Fully Adjustable 50" (standard) FA100 - Fully Adjustable 100" FA150 - Fully Adjustable 150" FA200 - Fully Adjustable 200" FA250 - Fully Adjustable 250" FA300 - Fully Adjustable 300" Ceiling Hardware Type C1 - 15/16" T-Bar C2 - 9/16" T-Bar C3 - Screw Slot C4 - Hard Ceiling C1T - 15/16" Tegular C2T - 9/16" Tegular | FE - Flat Endcap (standard) SW - Signal White (standard) FB - Finelite Black SA - Satin Aluminum #### - RAL Color Code * |

OTHER OPTIONS

| Emergency Style (Optional) | Integrated Sensor (Optional) | Special Options (Optional) |
|---|---|--|
| See page 5 Backup Battery table LGD18W - Legrand 18W Brand Battery Back-up LGD10W - Legrand 10W Brand Battery Back-up BSL310LP - Bodine Battery Back up Low Profile BSL10T3 - Bodine Battery Back up Low Profile Compact EM/GEN - Emergency to Generator NL - Night Light GTD - Generator Transfer Device ALCR - Automatic Load Control Relay See Backup Battery table on page 5 for fitment limitations | OBO - Occupancy OBD - Daylight W601 - Wattstopper Sensor ⁴ OBE - Enlighted Sensor ⁵ REE - Remote Enlighted CLM-99 - Encelium RF SLM-99 - Encelium Sensor | AOCC-W - Lutron Athena Sensor ⁶ (Device Color White) AOCC-B - Lutron Athena Sensor ⁶ (Device Color Black) ARF-W - Lutron Athena RF ⁶ (Device Color White) ARF-B - Lutron Athena RF ⁶ (Device Color Black) VOCC - Lutron Vive Sensor ⁷ VRF - Lutron Vive RF ⁷ CP - Chicago Plenum ⁸ RLA - Red List Approved RLD - Red List Declared |

¹ DLC not available

² Contact factory for switching options

³ Add DTO to gain "Dim to Off" functionality (FC-10% - DTO, FC-1% - DTO)

⁴ 20 business days lead time for color

⁵ LMFS-601 w/ 0-10V driver(s) and LMFI-111, up to 6 drivers may be connected.

⁶ LMFS-601 w/ Dali driver, only 1 driver can be connected.

⁶ Enlighted components installed by Finelite, provided by others

⁶ 0-10V Drivers - **AOCC** up to 10 drivers may be connected; **ARF** up to 40 driver may be connected

DALI Drivers - **AOCC** & **ARF** up to 4 drivers can be connected

⁷ Lutron Vive Ingrated Sensors require a DALI driver. Contact factory for Indirect Distribution.

⁸ Only available with C1, C2, and C3 mounting hardware with Finelite Gridbox

| | | |
|----------------|----------|-------|
| Submitted by: | | Date: |
| Type: | Project: | |
| Ordering Info: | | |

High Performance 3" Aperture (HP-3) Pendant

SUPPLEMENTARY DRIVER PAGE

0-10V Driver Options

| | |
|-----------------------|---|
| FC-10% | Factory Choice, 0-10V 10% Dimming (Linear) |
| FC-10%-DTO | Factory Choice, 0-10V 10% Dimming, Dim-to-Off (Linear) |
| FC-1% | Factory Choice, 0-10V 1% Dimming (Linear) |
| FC-1%-DTO | Factory Choice, 0-10V 1% Dimming, Dim-to-Off (Linear) |
| ELD-10V-0% | EldoLED SOLOdrive, 0-10V 0.1% Dimming (Linear) |
| ELD-10V-1% | EldoLED ECOdrive, 0-10V 1% Dimming (Linear) |
| 10V-TW-10% | EldoLED OTi, 0-10V 10% Dimming, <i>Tunable White</i> (Linear) |
| 10V-TW-10%-DTO | EldoLED OTi, 0-10V 10% Dimming, Dim-to-Off, <i>Tunable White</i> (Linear) |
| OTi-10% | EldoLED OTi, 0-10V 10% Dimming (Linear) |
| OTi-10%-DTO | EldoLED OTi, 0-10V 10% Dimming, Dim-to-Off (Linear) |
| OTi-1% | EldoLED OTi, 0-10V 1% Dimming (Linear) |
| OTi-1%-DTO | EldoLED OTi, 0-10V 1% Dimming, Dim-to-Off (Linear) |

DALI Driver Options

| | |
|--------------------|---|
| FC-DALI-1% | Factory Choice, DALI 1% Dimming (Logarithmic) |
| DXL-DALI-1% | EldoLED Dexal, DALI 1% Dimming (Logarithmic) |
| ELD-DALI-0% | EldoLED SOLOdrive, DALI 0.1% Dimming (Logarithmic) |
| ELD-DALI-1% | EldoLED ECOdrive, DALI 1% Dimming (Logarithmic) |
| ELD-DALI-TW | EldoLED DUALdrive Light Shape, DALI 0.1% Dimming, <i>Tunable White</i> (Logarithmic Dimming , Linear CCT Control) |

DMX Driver Options

| | |
|---------------------|---|
| ELD-DMX | EldoLED POWERdrive, DMX 0.1% Dimming (8 Bit, 1CH) (Linear) |
| ELD-DMX-16 | EldoLED POWERdrive, DMX 0.1% Dimming (16 Bit, 2CH) (Linear) |
| ELD-DMX-TW | EldoLED POWERdrive, DMX 0.1% Dimming, <i>Tunable White</i> (8 Bit, 2CH - CH1 Warm / CH2 Cool) (Linear) |
| ELD-DMX-TW16 | EldoLED POWERdrive, DMX 0.1% Dimming, <i>Tunable White</i> (16 Bit, 4CH - CH1, 2 Warm / CH3, 4 Cool) (Linear) |

Lutron Driver Options

| | |
|----------------|--|
| LUT-ES1 | Lutron, Ecosystem 1% Dimming |
| LUT-TW | Lutron LD2 Dali-2 1%, <i>Tunable White</i> |

| | | |
|----------------|----------|-------|
| Submitted by: | | Date: |
| Type: | Project: | |
| Ordering Info: | | |

High Performance 3" Aperture (HP-3) Pendant

SPECIFICATIONS

BODY TYPE

CONSTRUCTION: Precision-cut 6063-T6 extruded recycled aluminum body. Internal joiner system, plug-together wiring, standard.

LENGTHS: Any length, 2' minimum, in increments down to 1/16" (±1/32"). 12' maximum section length.

OUTPUT AND LED TYPE

LIGHT OUTPUT: Four lumen packages available, Standard (**S**), Boosted Standard (**B**), High (**H**), and Very High (**V**). For lengths 3' and greater, the uplight and downlight can be specified with different lumen packages and dual controls. For Tailored Outputs outside of range from Standard (**S**) to Very High (**V**), consult factory. Light engines are replaceable.

MECHANICAL/OPTICAL OPTIONS

UPLIGHT OPTION⁴: 12 ft. maximum diffuser length. 73% transmissive, 99% diffusion. Internal secondary diffusers at corners ensure visually seamless, uniform, continuous illumination options include: Flush frost white snap-in dif- fuser, 73% transmissive, 99% diffusion; Widespread Optic (**WSO**); WSO enables increased luminaire spacing with improved ceiling uniformity. Asymmetric optic directs light in a specific direction. **ASY-L** distributes light to the left, **ASY-R** distributed light to the right of the luminaire. Consult factory for more tailored lumen outputs.

DOWNLIGHT OPTION⁵: 12' maximum diffuser length. Flush frost white snap-in diffuser standard, 77% transmissive, 99% diffusion. Internal secondary diffusers at corners ensure visually seamless, uniform, continuous illumination. Available with Flush (**F**) and Bottom Glow (**BG**). Consult factory for more tailored lumen outputs.

LUMEN MAINTENANCE: 90% of initial light output (L90) at 100,000+ hours; 70% of initial light output (L70) at 200,000+ hours.

REFLECTORS: Die-formed 20-gauge cold-rolled steel reflectors finished in 96LG High Reflectance white powder coat paint.

ELECTRICAL OPTIONS

STATIC WHITE FEED: Standard with one 18-gauge/5-conductor single-circuit feed controlling uplight and downlight together (power and dimming). Specify dual feeds for independent control of uplight and downlight. 14-gauge feed used when luminaire current exceeds 5 amps.

TUNABLE WHITE FEED: Standard with one 18-gauge/5-conductor single-circuit feed. 14-gauge feed used when fixture current exceeds 5 amps. DMX feeds cannot be cut or spliced. DMX feeds should be ordered based on fixed lengths.

0-10V:

- One 18-gauge / 3-conductor power
- One 18-gauge / 4-conductor for dimming and controls

Dali:

- One 18-gauge / 5-conductor power and controls

DMX:

- One 18-gauge / 3-conductor power
- One DMX feed

STATIC WHITE DRIVER: Replaceable 120V, 277V, and 347V constant current reduction dimming driver standard. Can be wired dimming or non-dimming. 0-10V dimming controls with a range of 100%-10% standard. Dimming to 1% available. Separate dimming for uplight and downlight available. Driver is fully accessible from below the ceiling.

Power Factor: ≥ 0.9

Total Harmonic Distortion (THD): <20%

Expected driver lifetime: 100,000 hours

LUTRON DRIVER OPTIONS:

LUT-ES1 - Hi-lume 1% EcoSystem with Soft-On, Fade-to-Black dimming (LDE1 series).

TUNABLE WHITE DRIVER: Replaceable LED driver. Driver is accessible from below the ceiling. 120V and 277V.

Power factor: ≥0.90

Total Harmonic Distortion (THD): <20%

Dimming Range: 100%-10%

Expected driver lifetime.: 100,000 hours

LUTRON TUNABLE WHITE DRIVER OPTION:

LUT-TW - Lutron LD2 Dali-2 1%, Tunable White.

MOUNTING OPTIONS

HANGING HARDWARE: 50" Fully Adjustable (**FA**) steel-plated aircraft cable with safety stop hardware standard.

TUNABLE WHITE DMX HANGING HARDWARE: For grid ceiling applications the dual GridBox™ mounting is supplied (standard). For hard ceiling applications the ceiling mounting box is supplied (standard). DMX feeds cannot be cut or spliced. DMX feeds should be ordered based on fixed lengths. Available DMX pendant feed lengths are 5' (standard), 12', and 30'.

TUNABLE WHITE DMX INTERCONNECTION CABLES: Luminaires are prewired with plug-and-play interconnected cables to support easy plug-together joining of fixture runs. DMX to RJ45 adapters and an RJ45 terminator for every 32 DMX drivers are included.

OTHER OPTIONS

ENDCAPS: Flat diecast aluminum endcaps (**FE**) add 1/4" to each end of luminaire.

¹ Not available with Wall Wash

² Indirect/Direct and Direct only

³ White Cross Blade (WCB) baffles not available with custom angles. Available in 90 degrees only

⁴ Pendant Indirect/Direct, Pendant Regressed Indirect/Direct, and Pendant Indirect only

⁵ Pendant Indirect/Direct, Pendant Regressed Indirect/Direct, Pendant Direct, and Pendant Regressed Direct only

⁶ Pendant Regressed Indirect/Direct & Pendant Regressed Direct only

| | | |
|----------------|----------|-------|
| Submitted by: | | Date: |
| Type: | Project: | |
| Ordering Info: | | |

High Performance 3" Aperture (HP-3) Pendant

SPECIFICATIONS

EMERGENCY STYLE: Optional emergency to generator/inverter wiring, internal generator transfer switch, nightlight wiring, step- dimming driver, backup battery.

Backup Battery

| | Legrand 18W | Legrand 10W/ Bodine BSL310LP |
|---------------------|-------------|---------------------------------|
| HP3-P-ID | | |
| Min. Housing Length | 12' | 8' |
| EM Lumen Output | 2088 | 1243 |
| EM Section Illum. | 2' | 2' or 4' |

* Minimum fixture housing length for battery pack approved without sensor
The lumens are based on 835. For other CCT/CRI, refer to the Lumen Adjustment Factor table on page 6.

Bodine GTD and Legrand ALCR Min. Length

| Configuration | Min Length |
|----------------------|------------|
| Generator | ID-3' |
| Generator + OCC | ID-3' |
| Daylight | ID-3' |
| Generator + Daylight | ID-3' |

TUNABLE WHITE ELECTRICAL OPTIONS:

TW Driver Options

- **0-10V:** EM/GEN, GTD or Battery Back Up
- **DMX:** Battery Back Up
- **DALI:** EM/GEN, GTD or Battery Back Up
- **LUTRON:** EM/GEN, GTD or Battery Back Up

INTEGRATED SENSORS: Integrated PIR (Passive Infrared) Occupancy (**OBO**) or Daylight Sensors (**OBD**) available with Flush and Bottom Glow downlight diffusers. PIR sensors not recommended for stairwell applications. Refer to Occupancy Sensor & Daylight Sensor tech sheet and the Embedded Intelligence landing page for more information and additional sensor options.

FINISHES: Finelite Signal White (**SW**) powder coat, Finelite Black (RAL 9005) with semi gloss fine texture (**FB**), and Satin Aluminum (**SA**) are standard. Optional Adder: 179 RAL colors¹⁰ are available.

LABELS: Luminaire and electrical components are ETL-listed conforming to UL 1598 in the U.S.A. and CAN/CSA C22.2 No. 250.0 in Canada. In accordance with NEC Code 410.130 (G), this luminaire contains an internal driver disconnect. UL 924 and UL 2108 - PoE options available on request. These fixtures are rated for Damp Location. Chicago Plenum options available for C1, C2, or C3 suspension using our GridBox. Finelite products use electronic components that are RoHS compliant, and the mechanical components of the luminaire have been verified to not knowingly contain any restricted substances listed per RoHS Directive 2015/863. Consult factory for tailored lighting options. Finelite makes the specification process easy when putting healthier products on your projects. Simply add - **RLA** (Red List Approved) or - **RLD** (Red List Declared) to your part number.

WEIGHT¹¹: ID - 3.4 lb/ft

WARRANTY: 10-year performance-based warranty on all standard components. Optional accessories such as emergency battery packs are covered by their individual manufacturer warranties.

⁸ Available in Indirect/Direct Regressed & Direct Regressed only
⁹ Consult Finelite for Generator Transfer Device and Battery Backup fit
¹⁰ 20 business days lead time for color
¹¹ Excludes Battery Backup and Generator Transfer Device weight


| | | |
|----------------|----------|-------|
| Submitted by: | | Date: |
| Type: | Project: | |
| Ordering Info: | | |

High Performance 3" Aperture (HP-3) Pendant

Indirect/Direct Photometry - 4' Luminaire 3500K

HP3-P-ID-4'-V-V-835-F-F


Uplight: Flush / **Downlight:** Flush
Distribution: 46% Up (V) / 54% Down (V)
Efficacy: 132 lm/W
Uplight: 4159 lumens (1040 lumens/foot)
Downlight: 4883 lumens (1221 lumens/foot)
Total luminaire output: 9042 lumens (2261 lm/ft)
68.68 watts (171 W/ft)



CRI: 80 / CCT: 3500K
NLTL LM79 Report # REP-112524-01

HP3-P-ID-4'-V-V-835-WSO-F

Uplight: Widespread Optic / **Downlight:** Flush
Distribution: 42% Up (V) / 58% Down (V)
Efficacy: 133 lm/W
Uplight: 3830 lumens (958 lumens/foot)
Downlight: 5288 lumens (1322 lumens/foot)
Total luminaire output: 9118 lumens (2280 lm/ft)
68.78 watts (172 W/ft)



CRI: 80 / CCT: 3500K
NLTL LM79 Report # REP-112024-04

Total Light Output, 3500K, 80 CRI (Lumens) - 4' Luminaire

| | 1S ¹ | 1B ¹ | 1H ¹ | 1V ² |
|-----------------|--------------------|--------------------|--------------------|--------------------|
| 1S ¹ | 5023 [153% 47%↓] | 5702 [159% 41%↓] | 6127 [169% 31%↓] | 7188 [174% 26%↓] |
| 1B ¹ | 5605 [147% 52%↓] | 6284 [153% 47%↓] | 6709 [163% 37%↓] | 7770 [169% 31%↓] |
| 1H ¹ | 5970 [138% 62%↓] | 6649 [143% 57%↓] | 7074 [153% 47%↓] | 8135 [160% 40%↓] |
| 1V ² | 6880 [132% 68%↓] | 7599 [137% 63%↓] | 7984 [147% 53%↓] | 9042 [146% 54%↓] |

Light Output, 3500K, 80 CRI (Lumens Per Foot)

| | 1S ¹ | 1B ¹ | 1H ¹ | 1V ² |
|-----------------|-----------------|-----------------|-----------------|-----------------|
| 1S ¹ | 1256 | 1426 | 1532 | 1797 |
| 1B ¹ | 1401 | 1571 | 1677 | 1943 |
| 1H ¹ | 1493 | 1662 | 1769 | 2034 |
| 1V ² | 1720 | 1900 | 1996 | 2261 |

Power, 3500K (Watts Per Foot)

| | 1S ¹ | 1B ¹ | 1H ¹ | 1V ² |
|-----------------|-----------------|-----------------|-----------------|-----------------|
| 1S ¹ | 9.6 | 10.8 | 11.5 | 13.4 |
| 1B ¹ | 10.8 | 12.0 | 12.7 | 14.6 |
| 1H ¹ | 11.5 | 12.7 | 13.5 | 15.3 |
| 1V ² | 13.4 | 14.6 | 15.3 | 17.1 |

Efficacy, 3500K, 80 CRI (Lumens Per Watt)

| | 1S ¹ | 1B ¹ | 1H ¹ | 1V ² |
|-----------------|-----------------|-----------------|-----------------|-----------------|
| 1S ¹ | 131 | 133 | 133 | 135 |
| 1B ¹ | 130 | 131 | 132 | 133 |
| 1H ¹ | 130 | 131 | 131 | 133 |
| 1V ² | 129 | 130 | 130 | 132 |

S - Standard Output, B - Boosted Standard Output, H - High Output, V - Very High Output

¹ Family Correlation based on 4' luminaire 3500K Very High Output (V) test - 120V.

² Based on NLTL LM79 reports: REP-112524-01

Total Light Output, 3500K, 80 CRI (Lumens) - 4' Luminaire

| | 1S ¹ | 1B ¹ | 1H ¹ | 1V ² |
|-----------------|--------------------|--------------------|--------------------|--------------------|
| 1S ¹ | 5064 [153% 47%↓] | 5806 [159% 41%↓] | 6270 [169% 31%↓] | 7429 [174% 26%↓] |
| 1B ¹ | 5595 [147% 52%↓] | 6336 [153% 47%↓] | 6800 [163% 37%↓] | 7959 [169% 31%↓] |
| 1H ¹ | 5927 [138% 62%↓] | 6668 [143% 57%↓] | 7132 [153% 47%↓] | 8291 [160% 40%↓] |
| 1V ² | 6755 [132% 68%↓] | 7497 [137% 63%↓] | 7961 [147% 53%↓] | 9118 [153% 47%↓] |

Light Output, 3500K, 80 CRI (Lumens Per Foot)

| | 1S ¹ | 1B ¹ | 1H ¹ | 1V ² |
|-----------------|-----------------|-----------------|-----------------|-----------------|
| 1S ¹ | 1266 | 1452 | 1568 | 1857 |
| 1B ¹ | 1399 | 1584 | 1700 | 1990 |
| 1H ¹ | 1482 | 1667 | 1783 | 2073 |
| 1V ² | 1689 | 1874 | 1990 | 2280 |

Power, 3500K (Watts Per Foot)

| | 1S ¹ | 1B ¹ | 1H ¹ | 1V ² |
|-----------------|-----------------|-----------------|-----------------|-----------------|
| 1S ¹ | 9.6 | 10.8 | 11.5 | 13.4 |
| 1B ¹ | 10.8 | 12.0 | 12.7 | 14.6 |
| 1H ¹ | 11.5 | 12.7 | 13.5 | 15.3 |
| 1V ² | 13.4 | 14.6 | 15.3 | 17.2 |

Efficacy, 3500K, 80 CRI (Lumens Per Watt)

| | 1S ¹ | 1B ¹ | 1H ¹ | 1V ² |
|-----------------|-----------------|-----------------|-----------------|-----------------|
| 1S ¹ | 133 | 135 | 136 | 139 |
| 1B ¹ | 130 | 133 | 134 | 137 |
| 1H ¹ | 129 | 131 | 133 | 135 |
| 1V ² | 126 | 129 | 130 | 133 |

S - Standard Output, B - Boosted Standard Output, H - High Output, V - Very High Output

¹ Family Correlation based on 4' luminaire 3500K Very High Output (V) test - 120V.

² Based on NLTL LM79 reports: REP-112024-04

Wattage is Real Power. If you would like additional details to calculate Apparent Power, please contact your local Finelite representative.

Sample Lumen Adjustment Calculation

| Lumen Adjustment Factors 80 CRI | |
|---------------------------------|-------|
| 3000K | 0.974 |
| 3500K | 1.000 |
| 4000K | 1.038 |

High Output (H) / Standard Output (S), 4000K, 90 CRI

Lumen Adjustment Factor: 0.974

Total Light Output: 6127 lm x 0.974 = 5968 lm

Total Light Output per Foot: 1532 lm/ft x 0.974 = 1492 lm/ft.
watts/foot: 10.7 W/ft.

$$\text{Efficacy} = \frac{1492 \frac{\text{lm}}{\text{ft.}}}{11.5 \frac{\text{W}}{\text{ft.}}} = 130 \text{ lm/W}$$

| | | |
|----------------|----------|-------|
| Submitted by: | | Date: |
| Type: | Project: | |
| Ordering Info: | | |

0-10V Tunable White

Finelite's contractor friendly Tunable White luminaires are available at low cost, with powerful and simple 0-10V tuning and intensity controls.

TUNABLE WHITE FEATURES

- CCT range: 2700K - 6500K
- Dimming Range: 100% to 10%
- CRI Options: 80 CRI or 90 CRI

Note:
Dim to Off options available.

LUMINAIRE FAMILY MODIFICATIONS/RESTRICTIONS

| Direct | Section Lengths | | | | | | | | | | |
|------------------------------------|---|----|----|----|----|----|----|----|-----|-----|-----|
| | 2' | 3' | 4' | 5' | 6' | 7' | 8' | 9' | 10' | 11' | 12' |
| Output S,B,H,V Single Circuit | Rows can be comprised of 2'-12' sections. Tailored lengths available. | | | | | | | | | | |
| Integral Battery Backup (BSL310LP) | | | | | | | ✓ | | ✓ | | ✓ |
| Indirect/Direct | | | | | | | | | | | |
| Output S,B Single Circuit | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Integral Battery Backup (BSL310LP) | | | | | | | ✓ | | ✓ | | ✓ |
| Output H,V Single Circuit | | ✓ | | | | | ✓ | | | | ✓ |
| Integral Battery Not Available | Remote Battery backup solution available. Consult factory for tailored lighting options. | | | | | | | | | | |
| Output S,B,H,V Dual Circuit | | ✓ | | | | | ✓ | | | | ✓ |
| Integral Battery Not Available | Remote Battery backup solution available. Consult factory for tailored lighting options. | | | | | | | | | | |

EN/GEN sections available for all body lengths


PHOTOMETRY

Apply a power adjustment factor to calculate wattage usage


| POWER | CONVERSION FACTOR |
|-------|-------------------|
| | 1.1X |

(Example: a 50 watt luminaire in static white would draw 55 watts using 0-10V Tunable White)

DUAL FEED DETAIL



| WIRING LEGEND | | |
|---------------|---------|--------------|
| Black | Hot | Line Voltage |
| White | Neutral | Line Voltage |
| Green | Ground | |



| WIRING LEGEND | | |
|---------------|---------|----------|
| Pink | Dimming | 0-10V DC |
| Purple | Dimming | 0-10V DC |
| Orange | TW | 0-10V DC |
| Blue | TW | 0-10V DC |